



Indexable face mill 47.5° MFPN45, with bore, Ø D / number of teeth Z: 63/4 mm



Order data

Order number	222800 63/4
GTIN	4960664602353
Item class	250

Description

Version:

High performance face milling cutter with double-sided pentagonal indexable inserts. The combination of approach angle, chip chamber design as well as the geometries and cutting angles of the indexable inserts ensure outstanding metal removal rates, chip clearance, working life, and low cutting forces, and hence high cost-effectiveness.

Machining strategy: HPC

maximum cutting depth $a_{p\max}$: 6 mm

maximum external $\varnothing D_{\max}$: 76 mm

Overall length L_{tot} : 40 mm

Mounting bore \varnothing : 22 mm

suitable indexable insert: PN.. 1205

Insert screw: 229700

Technical description

Cutting edge $\varnothing D_c$	63 mm
Overall length L_{tot}	40 mm
suitable indexable insert	PN.. 1205
Clamp screw for shim	229702 (SW5; 6.0 Nm)

Mounting bore \varnothing	22 mm
maximum external $\varnothing D_{\max}$	76 mm
Shim	229750
maximum cutting depth $a_{p \max}$	6 mm
Insert screw	229700
Number of cutting edges Z	4
Shank type	with bore
Setting angle κ	47.5 degrees
Through-coolant	no
Machining strategy	HPC
Type of product	Indexable insert cutter

Accessories

Clamping screw	229702
Clamping screw	229700
Shim	229750