


**Indexable face mill 70° MFK, with bore, Ø D / number of teeth Z: 315/28 mm**

**Order data**

Order number	223300 315/28
GTIN	4960664732845
Item class	250

**Description**
**Version:**

Face mills for high-performance machining of cast iron. Close and very close tooth spacing for maximum productivity when machining cast iron.

**Advantage:**

- **Cost-effective and stable machining by use of 10-edge pentagonal inserts.**
- **Reduced cutting forces thanks to balanced tool design and high approach angle.**

Through-coolant: no

maximum cutting depth  $a_{p,max}$ : 6 mm

maximum external  $\varnothing D_{max}$ : 324 mm

Overall length  $L_{tot}$ : 63 mm

Mounting bore  $\varnothing$ : 60 mm

suitable indexable insert: PN.. 1106

Wedge: 229720

**Technical description**

Wedge screw	229721
maximum cutting depth $a_{p,max}$	6 mm

Number of cutting edges Z	28
maximum external $\varnothing D_{\max}$	324 mm
Mounting bore $\varnothing$	60 mm
Overall length $L_{\text{tot}}$	63 mm
Wedge	229720
suitable indexable insert	PN.. 1106
Cutting edge $\varnothing D_c$	315 mm
Shank type	with bore
Setting angle $\kappa$	70 degrees
Through-coolant	no
Type of product	Indexable insert cutter

---

## Accessories

Wedge screw	229721
Wedge	229720