


**Shoulder mill 90° MEW, Plain shank, Ø D / number of teeth Z: 40/3L mm**

**Order data**

Order number	225200 40/3L
GTIN	4960664648290
Item class	250

**Description**
**Version:**
**Cost-efficient due to 4 cutting edges.**

Through-coolant: yes

 maximum cutting depth  $a_{p\max}$ : 15 mm

 Overhang  $L_1$ : 50 mm

 Overall length  $L_{\text{tot}}$ : 150 mm

 Shank  $\varnothing D_s$  h6: 32 mm

suitable indexable insert: LOMU..

Indexable insert size: 15

**Technical description**

Cutting edge $\varnothing D_c$	40 mm
suitable indexable insert	LOMU..
Insert screw	229714 (15IP; 3.5 Nm)
Shank $\varnothing D_s$ h6	32 mm
Overall length $L_{\text{tot}}$	150 mm
Overhang $L_1$	50 mm
Indexable insert size	15
maximum cutting depth $a_{p\max}$	15 mm
Number of cutting edges Z	3
Shank type	Plain shank

Setting angle $\kappa$	90 degrees
Milling application	End milling
Milling application	Plunging
Through-coolant	yes
Type of product	Indexable insert cutter

---

## Accessories

Clamping screw	229714
----------------	--------