



Indexable milling cutter 90° MECX, Plain shank, Ø D / number of teeth Z: 17/3XL mm



Order data

Order number	227100 17/3XL
GTIN	4960664462681
Item class	250

Description

Description:

Very close spacing provides improved productivity even under more unstable machining conditions. Low cutting forces and high stability for low tendency to vibrate. Permits various milling tasks such as milling shoulders and ramps etc.

Through-coolant: yes

maximum cutting depth $a_{p\max}$: 6 mm

Overhang L_1 : 20 mm

Overall length L_{tot} : 130 mm

Shank Ø D_s h6: 16 mm

suitable indexable insert: BD.. 0703

Insert screw: 229707 (T6; 0.45 Nm)

Technical description

Shank Ø D_s h6	16 mm
Overall length L_{tot}	130 mm
Cutting edge Ø D_c	17 mm
Insert screw	229707 (T6; 0.45 Nm)
suitable indexable insert	BD.. 0703
maximum cutting depth $a_{p\max}$	6 mm
Overhang L_1	20 mm
Number of cutting edges Z	3

Shank type	Plain shank
Setting angle κ	90 degrees
Milling application	Circular milling
Milling application	Ramping
Milling application	End milling
Through-coolant	yes
Type of product	Indexable insert cutter

Accessories

Clamping screw	229707
----------------	--------