




## Indexable milling cutter 90° MECX, Weldon shank, Ø D / number of teeth Z: 20/5 mm



### Order data

Order number	227105 20/5
GTIN	4960664472680
Item class	250

### Description

#### Description:

Very close spacing provides improved productivity even under more unstable machining conditions. Low cutting forces and high stability for low tendency to vibrate. Permits various milling tasks such as milling shoulders and ramps etc.

Through-coolant: yes

maximum cutting depth  $a_{p,max}$ : 6 mm

Overhang  $L_1$ : 20 mm

Overall length  $L_{tot}$ : 81 mm

Shank Ø  $D_s$  h6: 20 mm

suitable indexable insert: BD.. 0703

Insert screw: 229707 (T6; 0.45 Nm)

### Technical description

Overhang $L_1$	20 mm
Shank Ø $D_s$ h6	20 mm
Overall length $L_{tot}$	81 mm
Cutting edge Ø $D_c$	20 mm
Insert screw	229707 (T6; 0.45 Nm)
suitable indexable insert	BD.. 0703
maximum cutting depth $a_{p,max}$	6 mm
Number of cutting edges Z	5

Shank type	Weldon shank
Setting angle $\kappa$	90 degrees
Milling application	Circular milling
Milling application	End milling
Milling application	Ramping
Through-coolant	yes
Type of product	Indexable insert cutter

---

## Accessories

Clamping screw	229707
----------------	--------