



Indexable milling cutter 90° MEC11T, Plain shank, Ø D / number of teeth Z: 20/3L mm



Order data

Order number	227300 20/3L
GTIN	4960664396061
Item class	250

Description

Description:

MEC11T mill type with higher stability due to lower number of cutters than MECX. This enables higher feed rates per cutter.

Through-coolant: yes

maximum cutting depth $a_{p,max}$: 10 mm

Overhang L_1 : 26 mm

Overall length L_{tot} : 110 mm

Shank Ø D_s h6: 16 mm

suitable indexable insert: BD.. 11T3

Insert screw: 229708 (T8; 1.2 Nm)

Technical description

Insert screw	229708 (T8; 1.2 Nm)
suitable indexable insert	BD.. 11T3
Shank Ø D_s h6	16 mm
maximum cutting depth $a_{p,max}$	10 mm
Overall length L_{tot}	110 mm
Overhang L_1	26 mm
Cutting edge Ø D_c	20 mm
Number of cutting edges Z	3
Shank type	Plain shank

Setting angle κ	90 degrees
Milling application	End milling
Milling application	Ramping
Milling application	Circular milling
Through-coolant	yes
Type of product	Indexable insert cutter

Accessories

Clamping screw	229708
----------------	--------