

Garant
HiPer-Drill base body, 1.5×D, Ø DC: 27 mm

Order data

Order number	231600 27
GTIN	4045197602664
Item class	21S

Description
Version:

- **Very high feed rates and maximum performance due to optimally matched geometries and materials.**
- **Precise positioning of the cutter insert due to Vee insert seating and secure clamping by the centre bore.**
- **High concentricity when assembled.**
- **Shank support for optimum stability in operation.**

Application:

For stationary and rotating use. For holes up to IT9 accuracy.

Note:

The insert screw must be replaced after every fifth change of cutter insert.

Further sizes up to Ø 50.99 mm available on request.

Clamp in a hydraulic chuck (such as No. 302026 size 20) for optimum radial run-out.

For optimum stability, clamp the drill so the overhang is as short as possible.

Number of cutting edges Z: 2

Dia. range D_c: 27 - 27.99 mm

Reach L₁: 42 mm

Shank Ø D_s: 32 mm

Shank length L_s: 60 mm

Clamping screw: 231999_15IP (5.0 Nm)

Technical description

Reach L ₁	42 mm
Shank Ø D _s	32 mm

Clamping screw	231999_15IP (5.0 Nm)
Dia. range D_c	27 - 27.99 mm
Shank length L_s	60 mm
Number of cutting edges Z	2
Drill depth up to	1.5×D
Shank	ISO 9766
Use for drilling	limited drilling with oblique exit
Use for drilling	limited drilling through a stack
Use for drilling	limited oblique spot drilling
Use for drilling	limited cross-drilling
Through-coolant	yes
Type of product	Indexable drill

Accessories

Torx Plus® screw Drive 15IP	231999 15IP
PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 15IP	674252 15IP
Torque screwdriver, fixed setting set torque 5,0 Nm	211750 5,0