

**Garant**
**HiPer-Drill base body, 5×D, Ø DC: 36 mm**

**Order data**

Order number	231610 36
GTIN	4045197726001
Item class	21S

**Description**
**Version:**

- **Very high feed rates and maximum performance due to optimally matched geometries and materials.**
- **Precise positioning of the cutter insert due to Vee insert seating and secure clamping by the centre bore.**
- **High concentricity when assembled.**
- **Shank support for optimum stability in operation.**

**Application:**

For stationary and rotating use. For holes up to IT9 accuracy.

**Note:**

The insert screw must be replaced after every fifth change of cutter insert.

Further sizes up to Ø 50.99 mm available on request.

Clamp in a hydraulic chuck (such as No. 302026 size 20) for optimum radial run-out.

For optimum stability, clamp the drill so the overhang is as short as possible.

Number of cutting edges Z: 2

Dia. range D<sub>c</sub>: 36 - 36.99 mm

Reach L<sub>1</sub>: 185 mm

Shank Ø D<sub>s</sub>: 32 mm

Shank length L<sub>s</sub>: 60 mm

Clamping screw: 231999\_20IP1 (7.5 Nm)

**Technical description**

Reach L <sub>1</sub>	185 mm
Clamping screw	231999_20IP1 (7.5 Nm)
Shank Ø D <sub>s</sub>	32 mm

Dia. range $D_c$	36 - 36.99 mm
Shank length $L_s$	60 mm
Number of cutting edges Z	2
Drill depth up to	5×D
Shank	ISO 9766
Use for drilling	limited drilling through a stack
Use for drilling	limited oblique spot drilling
Use for drilling	limited drilling with oblique exit
Use for drilling	limited cross-drilling
Through-coolant	yes
Type of product	Indexable drill

## Accessories

Torx Plus® screw Drive 20IP	231999 20IP
Torx Plus® screw Drive 20IP1	231999 20IP1
PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 20IP	674252 20IP
8 mm blade with magnet with 1/4 inch bit holder overall length 50 mm	659874 50
Torque screwdriver with scale, to take interchangeable blades maximum torque 1600 cNm	659906 1600