

**Garant**
**HiPer-Drill base body, 8×D, Ø DC: 11 mm**

**Order data**

Order number	231615 11
GTIN	4045197716286
Item class	21S

**Description**
**Version:**

- **Very high feed rates and maximum performance due to optimally matched geometries and materials.**
- **Precise positioning of the cutter insert due to Vee insert seating and secure clamping by the centre bore.**
- **High concentricity when assembled.**
- **Shank support for optimum stability in operation.**

Created by an additive procedure.

**Application:**

For stationary and rotating use. For holes up to IT9 accuracy.

**Recommendation:**

Drill the pilot hole.

**Note:**

Further sizes up to Ø 50.99 mm available on request.

The insert screw must be replaced after every fifth change of cutter insert.

reduce  $v_f$  values by 20 %.

Clamp in a hydraulic chuck (such as No. 302026 size 20) for optimum radial run-out.

For optimum stability, clamp the drill so the overhang is as short as possible.

For process reliability when using the drill, initial pilot drilling to 1.5×D with the drill No. 231600 with the same cutter insert size and type is necessary. **The generation of a pilot hole improves process reliability.**

Number of cutting edges Z: 2

Dia. range  $D_c$ : 11 - 11.49 mm

Reach  $L_1$ : 92 mm

Shank Ø  $D_s$ : 16 mm

Shank length  $L_s$ : 48 mm

Clamping screw: 231999\_6IP (0.4 Nm)

## Technical description

Reach $L_1$	92 mm
Clamping screw	231999_6IP (0.4 Nm)
Shank $\varnothing D_s$	16 mm
Dia. range $D_c$	11 - 11.49 mm
Shank length $L_s$	48 mm
Number of cutting edges Z	2
Drill depth up to	8×D
Shank	ISO 9766
Use for drilling	limited drilling with oblique exit
Use for drilling	limited drilling through a stack
Use for drilling	limited oblique spot drilling
Use for drilling	limited cross-drilling
Through-coolant	yes
Type of product	Indexable drill

## Accessories

Torx Plus® screw Drive 6IP	231999 6IP
8 mm blade with magnet with 1/4 inch bit holder overall length 50 mm	659874 50
PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 6IP	674252 6IP
Torque screwdriver with scale, to take interchangeable blades maximum torque 200 cNm	659906 200