

Garant
HiPer-Drill cutter insert h7, HB7630, Ø D: 24,7 mm

Order data

| | |
|--------------|---------------|
| Order number | 231650 24,7 |
| GTIN | 4045197606563 |
| Item class | 21M |

Description
Version:

Vee ground cutter inserts for precise positioning and stable seating.
Concentricity when assembled $\leq 20 \mu\text{m}$. For holes up to IT9 accuracy.

Note:

Cutting data applies for the base body $5 \times D$.

Drill pilot holes exclusively with cutter insert of the same type.

Semi-Standard: yes

for base body Ø D: 24 mm

Feed f in stainless steel $> 900 \text{ N/mm}^2$: 0.26 mm/rev.

Technical description

| | |
|--|--------------|
| Feed f in stainless steel $> 900 \text{ N/mm}^2$ | 0.26 mm/rev. |
| Ø D | 24.7 mm |
| for base body Ø D | 24 mm |
| Number of changes/inserts | 1 |

| | |
|---------------------------|--------------------------|
| Grade | HB7630 |
| Tool material | Carbide |
| Point angle | 135 degrees |
| Semi-Standard | yes |
| Number of cutting edges Z | 2 |
| Type of product | Cutter insert for boring |

Accessories

| | |
|-----------------------------|-------------|
| Torx Plus® screw Drive 10IP | 231999 10IP |
|-----------------------------|-------------|