



## Base body Parallel shank, with through-coolant, 1.5×D, Type: 36



### Order data

|              |               |
|--------------|---------------|
| Order number | 232240 36     |
| GTIN         | 4045197717764 |
| Item class   | 22G           |

### Description

#### Version:

With internal cooling.

#### Straight fluted.

#### Note:

Further sizes available on request.

Through-coolant: yes

Number of cutting edges Z: 2

Dia. range  $D_c$ : 36 - 47 mm

Reach  $L_1$ : 70.5 mm

Shank  $\varnothing D_s$ : 40 mm

Shank length  $L_s$ : 70 mm

Clamping screws: 232990 TX20

### Technical description

|                           |             |
|---------------------------|-------------|
| Reach $L_1$               | 70.5 mm     |
| Shank $\varnothing D_s$   | 40 mm       |
| Clamping screws           | 232990 TX20 |
| Dia. range $D_c$          | 36 - 47 mm  |
| Shank length $L_s$        | 70 mm       |
| Number of cutting edges Z | 2           |
| Drill depth up to         | 1.5×D       |

|                 |                 |
|-----------------|-----------------|
| Shank           | DIN 1835 B      |
| Through-coolant | yes             |
| Type of product | Indexable drill |

---

## Accessories

|   |             |
|---|-------------|
| Torx® set of screws 10 pieces Drive TX20  | 232990 TX20 |
| Torque screwdriver with scale, to take interchangeable blades maximum torque 1600 cNm | 659906 1600 |
| 8 mm blade with magnet with 1/4 inch bit holder overall length 50 mm                  | 659874 50   |
| PrecisionBit for Torx®, shank E 6.3 Torx® profile TX20                                | 674248 TX20 |