



Base body Parallel shank, with through-coolant, 12xD, Type: 36



Order data

Order number	232256 36
GTIN	4045197717825
Item class	22G

Description

Version:

With internal cooling. **Straight fluted.**

Note:

Reduce feed rates f by 10% and v_c values by 30%.

Further sizes available on request.

Through-coolant: yes

Number of cutting edges Z : 2

Dia. range D_c : 36 - 47 mm

Reach L_1 : 432 mm

Shank $\varnothing D_s$: 40 mm

Shank length L_s : 70 mm

Clamping screws: 232990 TX20

Technical description

Shank $\varnothing D_s$	40 mm
Clamping screws	232990 TX20
Reach L_1	432 mm
Dia. range D_c	36 - 47 mm
Shank length L_s	70 mm
Number of cutting edges Z	2
Drill depth up to	12xD
Shank	DIN 1835 B
Through-coolant	yes

Type of product	Indexable drill
-----------------	-----------------

Accessories

8 mm blade with magnet with 1/4 inch bit holder overall length 50 mm	659874 50
Torx® set of screws 10 pieces Drive TX20	232990 TX20
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX20	674248 TX20
Torque screwdriver with scale, to take interchangeable blades maximum torque 1600 cNm	659906 1600