

Garant
Indexable drill combination shank, 2xD, Ø DC: 23 mm

Order data

Order number	232298 23
GTIN	4045197676955
Item class	21S

Description
Version:
High stability and very high process reliability.
Application:
For stationary and rotating application.

 For holes free of withdrawal scoring and exact dimensional accuracy (approx. ± 0.1 mm).

Also suitable for machines with low drive power. Especially for **MTC (Multi Task Cutting)** use on the new generation of turning/milling centres (**MTM**).

With indexable inserts No. 232400 – 232780.

Note:
CAUTION!

A disc falls off when the drill exits.

Risk of injury if the component is rotating.

Please take safety precautions.

Counterboring tools with up to 2 steps to your specification available on request.
(Minimum order quantity: 2 pieces)

for inch Ø: 29/32 inch

 Overhang L_A : 70 mm

 Shank Ø D_s : 25 mm

 Shank length L_s : 56 mm

 Maximum adjustment limit V_{max} : 0.5 mm

ISO code indexable insert: WOEX 040304

Technical description

Number of cutting edges Z	1
Pack of insert screws	239700 6IP1 (1.0 Nm)

ISO code indexable insert	WOEX 040304
Shank $\varnothing D_s$	25 mm
Reach L_1	46 mm
Shank length L_s	56 mm
Nominal $\varnothing D$	23
for inch \varnothing	29/32 inch
Maximum adjustment limit V_{max}	0.5 mm
Overhang L_A	70 mm
Drill depth for indexable insert drill up to	2×D
Shank	DIN 6535 HE, DIN 6595
Use for drilling	Centre drilling
Use for drilling	oblique spot drilling
Use for drilling	limited cross-drilling
Use for drilling	limited drilling through a stack
Use for drilling	Aperture
Use for drilling	oblique exit
Use for drilling	convex
Through-coolant	yes
Machining strategy	MTC

Accessories

Torque screwdriver, fixed setting set torque 1,0 Nm	211750 1,0
Torx Plus® insert screw set 10 pieces Drive 6IP1	239700 6IP1
PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 6IP	674252 6IP