

**Garant****Indexable drill combination shank, 2xD, Ø DC: 41 mm****Order data**

Order number	232298 41
GTIN	4045197677143
Item class	21S

**Description****Version:****High stability and very high process reliability.****Application:****For stationary and rotating application.**For holes free of withdrawal scoring and exact dimensional accuracy (approx.  $\pm 0.1$  mm).**Also suitable for machines with low drive power.** Especially for **MTC (Multi Task Cutting)** use on the new generation of turning/milling centres (**MTM**).

With indexable inserts No. 232400 – 232780.

**Note:****CAUTION!**

A disc falls off when the drill exits.

Risk of injury if the component is rotating.

Please take safety precautions.

**Counterboring tools with up to 2 steps to your specification available on request.****(Minimum order quantity: 2 pieces)**Overhang  $L_A$ : 121 mmShank  $\varnothing D_s$ : 32 mmShank length  $L_s$ : 60 mmMaximum adjustment limit  $V_{max}$ : 1.5 mm

ISO code indexable insert: WOEX 06T304

Pack of insert screws: 239700 10IP (2.8 Nm)

**Technical description**

ISO code indexable insert	WOEX 06T304
Shank $\varnothing D_s$	32 mm

Number of cutting edges Z	1
Reach L <sub>1</sub>	82 mm
Pack of insert screws	239700 10IP (2.8 Nm)
Shank length L <sub>s</sub>	60 mm
Nominal Ø D	41
Maximum adjustment limit V <sub>max</sub>	1.5 mm
Overhang L <sub>A</sub>	121 mm
Drill depth for indexable insert drill up to	2×D
Shank	DIN 6535 HE, DIN 6595
Use for drilling	Centre drilling
Use for drilling	oblique spot drilling
Use for drilling	limited cross-drilling
Use for drilling	limited drilling through a stack
Use for drilling	Aperture
Use for drilling	oblique exit
Use for drilling	convex
Through-coolant	yes
Machining strategy	MTC

## Accessories

PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 10IP	674252 10IP
Torque screwdriver, fixed setting set torque 2,8 Nm	211750 2,8
Torx Plus® insert screw set 10 pieces Drive 10IP	239700 10IP