

Garant
GARANT Power Drill indexable drill Combination shank, 2xD, Ø DC: 15 mm

Order data

Order number	234000 15
GTIN	4045197739070
Item class	21S

Description
Version:

The helical coolant ducts ensure very high stability, since they do not weaken the core of the drill.

Bore tolerance: $-0.1 / +0.3$ mm

Description:

For maximum performance and dimensional accuracy. Even for very difficult drilling situations up to $5 \times D$.

Application:

With indexable inserts No. 234030 - 234098.

Use of the advertising text:

With inserts No. GG2340 - GG2389.

Note:

Other intermediate sizes in 1/10 increments available on request.

for inch Ø: 19/32 inch

Overhang L_A : 44 mm

Shank Ø D_s : 20 mm

Shank length L_s : 50 mm

Maximum adjustment limit V_{max} : 0.25 mm

ISO code indexable insert: SOGX 050204

Technical description

Shank length L_s	50 mm
Shank Ø D_s	20 mm
Reach L_1	30 mm

ISO code indexable insert	SOGX 050204
Pack of insert screws	239700 5IP (0.38 Nm)
Number of cutting edges Z	1
Series	GARANT Power Drill
Nominal \varnothing D	15
for inch \varnothing	19/32 inch
Maximum adjustment limit V_{\max}	0.25 mm
Overhang L_A	44 mm
Drill depth for indexable insert drill up to	2xD
Shank	ISO 9766
Use for drilling	limited centre drilling
Use for drilling	limited convexity
Use for drilling	limited cross-drilling
Use for drilling	limited drilling through a stack
Use for drilling	limited drilling with oblique exit
Use for drilling	limited cross-drilling
Through-coolant	yes
Machining strategy	HPC

Accessories

PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 5IP	674252 5IP
Torx Plus® insert screw set 10 pieces Drive 5IP	239700 5IP
Torque screwdriver, fixed setting set torque 0,38 Nm	211750 0,38