

Garant
GARANT Power Drill indexable drill Combination shank, 2xD, Ø DC: 30 mm

Order data

Order number	234000 30
GTIN	4045197739872
Item class	21S

Description
Version:

The helical coolant ducts ensure very high stability, since they do not weaken the core of the drill.

Bore tolerance: -0.1 / +0.3 mm

Description:

For maximum performance and dimensional accuracy. Even for very difficult drilling situations up to 5xD.

Application:

With indexable inserts No. 234030 - 234098.

Use of the advertising text:

With inserts No. GG2340 - GG2389.

Note:

Other intermediate sizes in 1/10 increments available on request.

Overhang L_A : 83 mm

Shank $\varnothing D_s$: 32 mm

Shank length L_s : 60 mm

Maximum adjustment limit V_{max} : 0.25 mm

ISO code indexable insert: SOGX 100408

Pack of insert screws: 239700 10IP (2.8 Nm)

Technical description

Reach L_1	60 mm
Shank length L_s	60 mm
ISO code indexable insert	SOGX 100408

Number of cutting edges Z	1
Pack of insert screws	239700 10IP (2.8 Nm)
Shank $\varnothing D_s$	32 mm
Series	GARANT Power Drill
Nominal $\varnothing D$	30
Maximum adjustment limit V_{max}	0.25 mm
Overhang L_A	83 mm
Drill depth for indexable insert drill up to	2xD
Shank	ISO 9766
Use for drilling	limited centre drilling
Use for drilling	limited convexity
Use for drilling	limited cross-drilling
Use for drilling	limited drilling through a stack
Use for drilling	limited drilling with oblique exit
Use for drilling	limited cross-drilling
Through-coolant	yes
Machining strategy	HPC

Accessories

PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 10IP	674252 10IP
Torque screwdriver, fixed setting set torque 2,8 Nm	211750 2,8
Torx Plus® insert screw set 10 pieces Drive 10IP	239700 10IP