

Garant
GARANT Power Drill indexable drill Combination shank, 3×D, Ø DC: 19 mm

Order data

Order number	234005 19
GTIN	4045197696489
Item class	21S

Description
Version:

The helical coolant ducts ensure very high stability, since they do not weaken the core of the drill.

Bore tolerance: $-0.1 / +0.3$ mm

Description:

For maximum performance and dimensional accuracy. Even for very difficult drilling situations up to 5×D.

Application:

With indexable inserts No. 234030 - 234098.

Use of the advertising text:

With inserts No. GG2340 - GG2389.

Note:

Other intermediate sizes in 1/10 increments available on request.

for inch Ø: 3/4 inch

Overhang L_A : 75 mm

Shank Ø D_s : 25 mm

Shank length L_s : 56 mm

Maximum adjustment limit V_{max} : 0.25 mm

ISO code indexable insert: SOGX 060305

Technical description

Number of cutting edges Z	1
Pack of insert screws	239700 6IP2 (0.6 Nm)
Reach L_1	57 mm

Shank $\varnothing D_s$	25 mm
ISO code indexable insert	SOGX 060305
Shank length L_s	56 mm
Series	GARANT Power Drill
Nominal $\varnothing D$	19
for inch \varnothing	3/4 inch
Maximum adjustment limit V_{max}	0.25 mm
Overhang L_A	75 mm
Drill depth for indexable insert drill up to	3xD
Shank	ISO 9766
Use for drilling	limited centre drilling
Use for drilling	limited convexity
Use for drilling	limited cross-drilling
Use for drilling	limited drilling through a stack
Use for drilling	limited drilling with oblique exit
Use for drilling	limited cross-drilling
Through-coolant	yes
Machining strategy	HPC

Accessories

PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 6IP	674252 6IP
Torque screwdriver, fixed setting set torque 0,6 Nm	211750 0,6
Torx Plus® insert screw set 10 pieces Drive 6IP2	239700 6IP2