


KOMET KUB Quatron® indexable drill Combination shank, 3×D, Ø DC: 16 mm

Order data

Order number	235502 16
GTIN	4047109024366
Item class	24P

Description
Version:
With combination shank.

- **Optimised coolant channels for reliable chip evacuation.**
- **Point angle 174° for almost flat-bottomed holes.**

Application:

- **For stationary and rotating use.**
- **For difficult drilling conditions (rolling scale, sloping surfaces of castings, interrupted cutting).**
- **For bores with tolerance ± 0.2 mm.**

With indexable inserts No. 236520 – 236576.

Supplied with:

Clamp screws (without indexable inserts).

Note:

Further sizes available on request.

Overhang L_A : 72 mm

Shank $\varnothing D_s$: 20 mm

Shank length L_s : 50 mm

ISO code indexable insert: SOEX 050204 13-..

Pack of insert screws: 239652 6IP1 (0.6 Nm)

Technical description

ISO code indexable insert	SOEX 050204 13-..
Pack of insert screws	239652 6IP1 (0.6 Nm)
Shank $\varnothing D_s$	20 mm
Number of cutting edges Z	1

Reach L ₁	48 mm
Shank length L _s	50 mm
Series	KUB Quatron®
Nominal Ø D	16
Overhang L _A	72 mm
Drill depth for indexable insert drill up to	3×D
Shank	DIN 6535 HE, DIN 6595
Use for drilling	Centre drilling
Use for drilling	limited cross-drilling
Use for drilling	oblique spot drilling
Use for drilling	Cross-drilling
Use for drilling	Centre drilling
Use for drilling	Aperture
Use for drilling	oblique exit
Use for drilling	convex
Through-coolant	yes

Accessories

Torx Plus® insert screw set 10 pieces Drive 6IP1	239652 6IP1
Torque screwdriver, fixed setting set torque 0,6 Nm	211750 0,6
PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 6IP	674252 6IP