


KOMET KUB Quatron® indexable drill Combination shank, 3×D, Ø DC: 39 mm

Order data

Order number	235502 39
GTIN	4047109026506
Item class	24P

Description
Version:
With combination shank.

- **Optimised coolant channels for reliable chip evacuation.**
- **Point angle 174° for almost flat-bottomed holes.**

Application:

- **For stationary and rotating use.**
- **For difficult drilling conditions (rolling scale, sloping surfaces of castings, interrupted cutting).**
- **For bores with tolerance ± 0.2 mm.**

With indexable inserts No. 236520 – 236576.

Supplied with:

Clamp screws (without indexable inserts).

Note:

Further sizes available on request.

Overhang L_A : 156 mm

Shank $\varnothing D_s$: 32 mm

Shank length L_s : 60 mm

ISO code indexable insert: SOEX 120508 44-..

Pack of insert screws: 239652 20IP (6.3 Nm)

Technical description

Reach L_1	117 mm
Number of cutting edges Z	1
Pack of insert screws	239652 20IP (6.3 Nm)
Shank $\varnothing D_s$	32 mm

ISO code indexable insert	SOEX 120508 44-..
Shank length L _s	60 mm
Series	KUB Quatron®
Nominal Ø D	39
Overhang L _A	156 mm
Drill depth for indexable insert drill up to	3×D
Shank	DIN 6535 HE, DIN 6595
Use for drilling	Centre drilling
Use for drilling	limited cross-drilling
Use for drilling	oblique spot drilling
Use for drilling	Cross-drilling
Use for drilling	Centre drilling
Use for drilling	Aperture
Use for drilling	oblique exit
Use for drilling	convex
Through-coolant	yes

Accessories

Torx Plus® insert screw set 10 pieces Drive 20IP	239652 20IP
8 mm blade with magnet with 1/4 inch bit holder overall length 50 mm	659874 50
Torque screwdriver with scale, to take interchangeable blades maximum torque 1600 cNm	659906 1600
PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 20IP	674252 20IP