



KUB Pentron® indexable drill Plain shank, 4×D, Ø DC: 16,5 mm



Order data

Order number	236601 16,5
GTIN	4047109194267
Item class	24P

Description

Version:

- **Very high performance and long tool life thanks to optimised base body strength and special surface treatment.**
- **Best dimensional accuracy even under very difficult drilling conditions.**
- **Stock costs reduced because internal and external inserts are identical.**

Bore tolerance: ØD – 0.1 / + 0.3

Application:

- **Under extreme machining conditions.**

With indexable inserts No. 236605 – 236610.

Supplied with:

Clamp screws (without indexable inserts).

Note:

Version 2×D and 3×D with ABS® also available on request in imperial sizes.

Version with PSC shank available on request.

Overhang L_A : 85 mm

Shank Ø D_s : 20 mm

Shank length L_s : 50 mm

ISO code indexable insert: SOGX 050204 12-...

Pack of insert screws: 239652 6IP1 (0.6 Nm)

Technical description

ISO code indexable insert	SOGX 050204 12-...
Pack of insert screws	239652 6IP1 (0.6 Nm)
Shank Ø D_s	20 mm

Reach L_1	68 mm
Number of cutting edges Z	1
Shank length L_s	50 mm
Series	KUB Pentron®
Nominal $\varnothing D$	16.5
Overhang L_A	85 mm
Drill depth for indexable insert drill up to	4×D
Shank	ISO 9766
Use for drilling	limited centre drilling
Use for drilling	limited convexity
Use for drilling	limited cross-drilling
Use for drilling	limited drilling through a stack
Use for drilling	limited drilling with oblique exit
Use for drilling	limited cross-drilling
Through-coolant	yes
Machining strategy	HPC

Accessories

Torx Plus® insert screw set 10 pieces Drive 6IP1	239652 6IP1
Torque screwdriver, fixed setting set torque 0,6 Nm	211750 0,6
PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 6IP	674252 6IP