



## KUB Pentron® indexable drill Plain shank, 4×D, Ø DC: 22 mm



### Order data

Order number	236601 22
GTIN	4047109181533
Item class	24P

### Description

#### Version:

- **Very high performance and long tool life thanks to optimised base body strength and special surface treatment.**
- **Best dimensional accuracy even under very difficult drilling conditions.**
- **Stock costs reduced because internal and external inserts are identical.**

**Bore tolerance:**  $\varnothing D - 0.1 / + 0.3$

#### Application:

- **Under extreme machining conditions.**

With indexable inserts No. 236605 – 236610.

#### Supplied with:

Clamp screws (without indexable inserts).

#### Note:

Version 2×D and 3×D with ABS® also available on request in imperial sizes.

Version with PSC shank available on request.

Overhang  $L_A$ : 107 mm

Shank  $\varnothing D_s$ : 25 mm

Shank length  $L_s$ : 56 mm

ISO code indexable insert: SOGX 07T208 20-...

Pack of insert screws: 239652 6IP2 (1.0 Nm)

### Technical description

Shank $\varnothing D_s$	25 mm
Reach $L_1$	88 mm
Number of cutting edges Z	1

Pack of insert screws	239652 6IP2 (1.0 Nm)
ISO code indexable insert	SOGX 07T208 20-...
Shank length L <sub>s</sub>	56 mm
Series	KUB Pentron®
Nominal Ø D	22
Overhang L <sub>A</sub>	107 mm
Drill depth for indexable insert drill up to	4×D
Shank	ISO 9766
Use for drilling	limited centre drilling
Use for drilling	limited convexity
Use for drilling	limited cross-drilling
Use for drilling	limited drilling through a stack
Use for drilling	limited drilling with oblique exit
Use for drilling	limited cross-drilling
Through-coolant	yes
Machining strategy	HPC

## Accessories

Torx Plus® insert screw set 10 pieces Drive 6IP2	239652 6IP2
Torque screwdriver, fixed setting set torque 1,0 Nm	211750 1,0
PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 6IP	674252 6IP