KOMET °

KUB Pentron[®] indexable drill Plain shank, 4×D, Ø DC: 28,5 mm



Order data

Order number	236601 28,5
GTIN	4047109194434
Item class	24P

Description

Version:

• Very high performance and long tool life thanks to optimised base body strength and special surface treatment.

· Best dimensional accuracy even under very difficult drilling conditions.

• Stock costs reduced because internal and external inserts are identical.

Bore tolerance: $\varnothing D - 0.1 / + 0.3$

Application:

· Under extreme machining conditions.

With indexable inserts No. 236605 – 236610.

Supplied with:

Clamp screws (without indexable inserts).

Note:

Version 2×D and 3×D with ABS[°] also available on request in imperial sizes.

Version with PSC shank available on request.

for inch Ø: 1 1/8 inch

Overhang L_A: 139 mm

Shank Ø D_s: 32 mm

Shank length L_s: 60 mm

ISO code indexable insert: SOGX 09T308 28-...

Pack of insert screws: 239652 8IP6 (2.2 Nm)

Technical description

Reach L ₁	116 mm
ISO code indexable insert	SOGX 09T308 28
Shank Ø D _s	32 mm

© Hoffmann GmbH Qualitätswerkzeuge

. . .

. .

1
239652 8IP6 (2.2 Nm)
60 mm
KUB Pentron®
28.5
1 1/8 inch
139 mm
4×D
ISO 9766
limited centre drilling
limited convexity
limited cross-drilling
limited drilling through a stack
limited drilling with oblique exit
limited cross-drilling
yes
HPC

Accessories

PrecisionBit for Torx Plus [®] , shank E 6.3 Torx Plus [®] profile 8IP	674252 8IP
Torque screwdriver, fixed setting set torque 2,2 Nm	211750 2,2
Torx Plus [®] insert screw set 10 pieces Drive 8IP6	239652 8IP6