KOMET.

KUB Pentron® indexable drill Plain shank, 4×D, Ø DC: 38 mm



Order data

Order number	236601 38
GTIN	4047109201439
Item class	24P

Description

Version:

- · Very high performance and long tool life thanks to optimised base body strength and special surface treatment.
- · Best dimensional accuracy even under very difficult drilling conditions.
- · Stock costs reduced because internal and external inserts are identical.

Bore tolerance: $\emptyset D - 0.1 / + 0.3$

Application:

· Under extreme machining conditions.

With indexable inserts No. 236605 – 236610.

Supplied with:

Clamp screws (without indexable inserts).

Note:

Version 2×D and 3×D with ABS[®] also available on request in imperial sizes.

Version with PSC shank available on request.

for inch Ø: 1 1/2 inch Overhang L_A: 179 mm Shank Ø D_s: 40 mm Shank length L_s: 68 mm

ISO code indexable insert: SOGX 120408 42-... Pack of insert screws: 239652 20IP (6.3 Nm)

Technical description

Reach L ₁	152 mm
ISO code indexable insert	SOGX 120408 42
Pack of insert screws	239652 20IP (6.3 Nm)



Number of cutting edges Z	1
Shank Ø D₅	40 mm
Shank length L _s	68 mm
Series	KUB Pentron®
Nominal Ø D	38
for inch \varnothing	1 1/2 inch
Overhang L _A	179 mm
Drill depth for indexable insert drill up to	4×D
Shank	ISO 9766
Use for drilling	limited centre drilling
Use for drilling	limited convexity
Use for drilling	limited cross-drilling
Use for drilling	limited drilling through a stack
Use for drilling	limited drilling with oblique exit
Use for drilling	limited cross-drilling
Through-coolant	yes
Machining strategy	HPC

Accessories

Torx Plus® insert screw set 10 pieces Drive 20IP	239652 20IP
Torque screwdriver with scale, to take interchangeable blades maximum torque 1600 cNm	659906 1600
8 mm blade with magnet with 1/4 inch bit holder overall length 50 mm	659874 50
PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 20IP	674252 20IP