


KUB Pentron® indexable drill ABS® shank, 5×D, Ø DC: 44,5 mm

Order data

| | |
|--------------|---------------|
| Order number | 236604 44,5 |
| GTIN | 4047109204676 |
| Item class | 24P |

Description
Version:
Bore tolerance: D – 0.1 / + 0.35

Application:

With indexable inserts No. 236605 – 236610.

Recommendation:
When spot-drilling reduce the feed rate by 70 %.

Note:

- **For use only under stable machining conditions.**
- **Version 2×D and 3×D with ABS® shank available on request.**
- **Offset-axis drilling is possible up to $V_{max} = 0.25$ mm, e.g. with eccentric adjusting unit No. 239010 to 239012.**
- **Maximum $\varnothing = D + 0.5$ mm achievable by offsetting.**
- **Version with PSC shank available on request.**

 for inch \varnothing : 1 3/4 inch

 Overhang L_A : 271 mm

 ABS® shank $\varnothing D_s$: 63 mm

ISO code indexable insert: SOGX 130508 46-...

Pack of insert screws: 239652 20IP (6.3 Nm)

Technical description

| | |
|------------------------------|----------------------|
| Reach L_1 | 225 mm |
| Number of cutting edges Z | 1 |
| Pack of insert screws | 239652 20IP (6.3 Nm) |
| ABS® shank $\varnothing D_s$ | 63 mm |

| | |
|--|------------------------------------|
| ISO code indexable insert | SOGX 130508 46-... |
| Series | KUB Pentron® |
| Nominal Ø D | 44.5 |
| for inch Ø | 1 3/4 inch |
| Overhang L _A | 271 mm |
| Drill depth for indexable insert drill up to | 5×D |
| Shank | ABS |
| Use for drilling | limited centre drilling |
| Use for drilling | limited convexity |
| Use for drilling | limited cross-drilling |
| Use for drilling | limited drilling through a stack |
| Use for drilling | limited drilling with oblique exit |
| Use for drilling | limited cross-drilling |
| Through-coolant | yes |
| Machining strategy | HPC |

Accessories

| | |
|---|-------------|
| 8 mm blade with magnet with 1/4 inch bit holder overall length 50 mm | 659874 50 |
| Torx Plus® insert screw set 10 pieces Drive 20IP | 239652 20IP |
| PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 20IP | 674252 20IP |
| Torque screwdriver with scale, to take interchangeable blades maximum torque 1600 cNm | 659906 1600 |