KOMET .

KUB Pentron[®] indexable drill Plain shank, 2×D, Ø DC: 24,5 mm



Order data

| Order number | 236614 24,5 |
|--------------|---------------|
| GTIN | 4047109277960 |
| Item class | 24P |

Description

Version:

Bore tolerance: $\varnothing D - 0.1 / + 0.2$

• Very high performance and long tool life thanks to optimised base body strength and special surface treatment.

· Best dimensional accuracy even under very difficult drilling conditions.

• Stock costs reduced because internal and external inserts are identical.

Application:

· Under extreme machining conditions.

With indexable inserts No. 236605 – 236610.

Supplied with:

Clamp screws (without indexable inserts).

Note:

Version $2 \times D$ and $3 \times D$ with ABS[°] also available on request in imperial sizes.

Version with PSC shank available on request.

Overhang L_A: 71 mm

Shank Ø D_s: 32 mm

Shank length L_s: 60 mm

ISO code indexable insert: SOGX 080308 24-...

Pack of insert screws: 239652 8IP1 (1.3 Nm)

Technical description

| Shank Ø D _s | 32 mm |
|---------------------------|-------|
| Number of cutting edges Z | 1 |
| Reach L ₁ | 50 mm |

| Shank length L _s | 60 mm |
|--|------------------------------------|
| Pack of insert screws | 239652 8IP1 (1.3 Nm) |
| ISO code indexable insert | SOGX 080308 24 |
| Series | KUB Pentron® |
| Nominal Ø D | 24.5 |
| Overhang L _A | 71 mm |
| Drill depth for indexable insert drill up to | 2×D |
| Shank | ISO 9766 |
| Use for drilling | limited centre drilling |
| Use for drilling | limited convexity |
| Use for drilling | limited cross-drilling |
| Use for drilling | limited drilling through a stack |
| Use for drilling | limited drilling with oblique exit |
| Use for drilling | limited cross-drilling |
| Through-coolant | yes |
| Machining strategy | HPC |

Accessories

| PrecisionBit for Torx Plus [®] , shank E 6.3 Torx Plus [®] profile 8IP | 674252 8IP |
|---|-------------|
| Torque screwdriver, fixed setting set torque 1,3 Nm | 211750 1,3 |
| Torx Plus [®] insert screw set 10 pieces Drive 8IP1 | 239652 8IP1 |