



KUB Pentron® indexable drill Plain shank, 2×D, Ø DC: 25 mm



Order data

Order number	236614 25
GTIN	4047109277953
Item class	24P

Description

Version:

Bore tolerance: $\varnothing D - 0.1 / + 0.2$

- **Very high performance and long tool life thanks to optimised base body strength and special surface treatment.**
- **Best dimensional accuracy even under very difficult drilling conditions.**
- **Stock costs reduced because internal and external inserts are identical.**

Application:

- **Under extreme machining conditions.**

With indexable inserts No. 236605 – 236610.

Supplied with:

Clamp screws (without indexable inserts).

Note:

Version 2×D and 3×D with ABS® also available on request in imperial sizes.

Version with PSC shank available on request.

Overhang L_A : 71 mm

Shank $\varnothing D_s$: 32 mm

Shank length L_s : 60 mm

ISO code indexable insert: SOGX 080308 24-...

Pack of insert screws: 239652 8IP1 (1.3 Nm)

Technical description

Number of cutting edges Z	1
ISO code indexable insert	SOGX 080308 24-...
Shank $\varnothing D_s$	32 mm

Reach L_1	50 mm
Shank length L_s	60 mm
Pack of insert screws	239652 8IP1 (1.3 Nm)
Series	KUB Pentron®
Nominal $\varnothing D$	25
Overhang L_A	71 mm
Drill depth for indexable insert drill up to	2×D
Shank	ISO 9766
Use for drilling	limited centre drilling
Use for drilling	limited convexity
Use for drilling	limited cross-drilling
Use for drilling	limited drilling through a stack
Use for drilling	limited drilling with oblique exit
Use for drilling	limited cross-drilling
Through-coolant	yes
Machining strategy	HPC

Accessories

PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 8IP	674252 8IP
Torx Plus® insert screw set 10 pieces Drive 8IP1	239652 8IP1
Torque screwdriver, fixed setting set torque 1,3 Nm	211750 1,3