



## KUB Pentron® indexable drill Plain shank, 2×D, Ø DC: 43 mm



### Order data

Order number	236614 43
GTIN	4047109277588
Item class	24P

### Description

#### Version:

**Bore tolerance:**  $\varnothing D - 0.1 / + 0.2$

- **Very high performance and long tool life thanks to optimised base body strength and special surface treatment.**
- **Best dimensional accuracy even under very difficult drilling conditions.**
- **Stock costs reduced because internal and external inserts are identical.**

#### Application:

- **Under extreme machining conditions.**

With indexable inserts No. 236605 – 236610.

#### Supplied with:

Clamp screws (without indexable inserts).

#### Note:

Version 2×D and 3×D with ABS® also available on request in imperial sizes.

Version with PSC shank available on request.

Overhang  $L_A$ : 116 mm

Shank  $\varnothing D_s$ : 40 mm

Shank length  $L_s$ : 68 mm

ISO code indexable insert: SOGX 130508 46-...

Pack of insert screws: 239652 20IP (6.3 Nm)

### Technical description

Pack of insert screws	239652 20IP (6.3 Nm)
Number of cutting edges Z	1
Shank length $L_s$	68 mm

ISO code indexable insert	SOGX 130508 46-...
Shank $\varnothing D_s$	40 mm
Reach $L_1$	86 mm
Series	KUB Pentron®
Nominal $\varnothing D$	43
Overhang $L_A$	116 mm
Drill depth for indexable insert drill up to	2×D
Shank	ISO 9766
Use for drilling	limited centre drilling
Use for drilling	limited convexity
Use for drilling	limited cross-drilling
Use for drilling	limited drilling through a stack
Use for drilling	limited drilling with oblique exit
Use for drilling	limited cross-drilling
Through-coolant	yes
Machining strategy	HPC

## Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 1600 cNm	659906 1600
Torx Plus® insert screw set 10 pieces Drive 20IP	239652 20IP
PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 20IP	674252 20IP
8 mm blade with magnet with 1/4 inch bit holder overall length 50 mm	659874 50