KOMET.

KOMET KUB Trigon® indexable drill Combination shank, 3×D, Ø DC: 14 mm



Order data

Order number	236630 14
GTIN	4047109100091
Item class	24P

Description

Version:

- · Special manufacturing procedure for extremely large flutes with very high rigidity.
- Specific positioning of the indexable inserts for bores free of withdrawal marks and with precise dimensional stability (± 0.1 mm as a rule).
- Internal coolant supply is directed to the cutting edges (sophisticated geometry, ideal for minimum lubrication).
- · 3 10 bar coolant pressure is sufficient.
- For stationary and rotating applications.

Application:

With indexable inserts No. 236740 - 237080.

Supplied with:

Clamp screws (without indexable inserts).

Note:

- Note! A disc falls off when the drill exits. Risk of injury if the component is rotating! Please take safety precautions.
- On request left-hand cutting; 2×D, other Ø; special types torsional vibration damper for ABS giving low-vibration machining, with maximum tool life and minimum noise level.

Overhang L_A : 66 mm Shank Ø D_s : 25 mm Shank length L_s : 56 mm

achievable maximum \varnothing offset: 15 mm Maximum adjustment limit V_{max} : 0.5 mm ISO code indexable insert: WOEX 030204 10-...

Technical description



Number of cutting edges Z	1
ISO code indexable insert	WOEX 030204 10
Pack of insert screws	239652 6IP1 (0.6 Nm)
Reach L ₁	42 mm
Shank Ø D _s	25 mm
achievable maximum Ø offset	15 mm
Shank length L _s	56 mm
Series	KUB Trigon®
Nominal Ø D	14
Maximum adjustment limit V_{max}	0.5 mm
Overhang L _A	66 mm
Drill depth for indexable insert drill up to	3×D
Shank	DIN 6535 HE, DIN 6595
Use for drilling	Centre drilling
Use for drilling	limited cross-drilling
Use for drilling	oblique spot drilling
Use for drilling	limited cross-drilling
Use for drilling	Aperture
Use for drilling	oblique exit
Use for drilling	convex
Through-coolant	yes

Accessories

Torque screwdriver, fixed setting set torque 0,6 Nm	211750 0,6
Torx Plus® insert screw set 10 pieces Drive 6IP1	239652 6IP1
PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 6IP	674252 6IP