#### KOMET .

# KOMET KUB Trigon<sup>®</sup> indexable drill Combination shank, 3×D, Ø DC: 19,5 mm



### Order data

Order number	236630 19,5
GTIN	4047109100183
Item class	24P

### Description

#### Version:

- · Special manufacturing procedure for extremely large flutes with very high rigidity.
- Specific positioning of the indexable inserts for bores free of withdrawal marks and with precise dimensional stability (± 0.1 mm as a rule).
- Internal coolant supply is directed to the cutting edges (sophisticated geometry, ideal for minimum lubrication).
- · 3 10 bar coolant pressure is sufficient.
- For stationary and rotating applications.

#### **Application:**

With indexable inserts No. 236740 - 237080.

#### **Supplied with:**

Clamp screws (without indexable inserts).

Note:

- Note! A disc falls off when the drill exits. Risk of injury if the component is rotating! Please take safety precautions.
- On request left-hand cutting; 2×D, other Ø; special types torsional vibration damper for ABS giving low-vibration machining, with maximum tool life and minimum noise level.

Overhang  $L_A$ : 84 mm Shank Ø D<sub>s</sub>: 25 mm Shank length L<sub>s</sub>: 56 mm achievable maximum Ø offset: 20 mm Maximum adjustment limit V<sub>max</sub>: 0.25 mm ISO code indexable insert: WOEX 030204 10-...

# **Technical description**

# not the second s

# Data sheet

ISO code indexable insert	WOEX 030204 10
Pack of insert screws	239652 6lP1 (0.6 Nm)
Number of cutting edges Z	1
achievable maximum Ø offset	20 mm
Reach L <sub>1</sub>	60 mm
Shank Ø D <sub>s</sub>	25 mm
Shank length L <sub>s</sub>	56 mm
Series	KUB Trigon®
Nominal Ø D	19.5
Maximum adjustment limit V <sub>max</sub>	0.25 mm
Overhang L <sub>A</sub>	84 mm
Drill depth for indexable insert drill up to	3×D
Shank	DIN 6535 HE, DIN 6595
Use for drilling	Centre drilling
Use for drilling	limited cross-drilling
Use for drilling	oblique spot drilling
Use for drilling	limited cross-drilling
Use for drilling	Aperture
Use for drilling	oblique exit
Use for drilling	convex
Through-coolant	yes

# Accessories

PrecisionBit for Torx Plus <sup>®</sup> , shank E 6.3 Torx Plus <sup>®</sup> profile 6IP	674252 6IP
Torque screwdriver, fixed setting set torque 0,6 Nm	211750 0,6
Torx Plus <sup>®</sup> insert screw set 10 pieces Drive 6IP1	239652 6IP1