




KOMET KUB Trigon® indexable drill Combination shank, 3×D, Ø DC: 24,5 mm



Order data

| | |
|--------------|---------------|
| Order number | 236630 24,5 |
| GTIN | 4047109100251 |
| Item class | 24P |

Description

Version:

- **Special manufacturing procedure for extremely large flutes with very high rigidity.**
- **Specific positioning of the indexable inserts for bores free of withdrawal marks and with precise dimensional stability (± 0.1 mm as a rule).**
- **Internal coolant supply is directed to the cutting edges (sophisticated geometry, ideal for minimum lubrication).**
- **3 – 10 bar coolant pressure is sufficient.**
- **For stationary and rotating applications.**

Application:

With indexable inserts No. 236740 – 237080.

Supplied with:

Clamp screws (without indexable inserts).

Note:

- **Note! A disc falls off when the drill exits. Risk of injury if the component is rotating! Please take safety precautions.**
- **On request – left-hand cutting; – 2×D, – other Ø; – special types – torsional vibration damper for ABS giving low-vibration machining, with maximum tool life and minimum noise level.**

Overhang L_A : 99 mm

Shank $\varnothing D_s$: 25 mm

Shank length L_s : 56 mm

achievable maximum \varnothing offset: 25.5 mm

Maximum adjustment limit V_{max} : 0.5 mm

ISO code indexable insert: WOEX 040304 18-...

Technical description

| | |
|--|------------------------|
| Pack of insert screws | 239652 6IP2 (1.0 Nm) |
| Reach L_1 | 75 mm |
| Number of cutting edges Z | 1 |
| Shank $\varnothing D_s$ | 25 mm |
| ISO code indexable insert | WOEX 040304 18-... |
| achievable maximum \varnothing offset | 25.5 mm |
| Shank length L_s | 56 mm |
| Series | KUB Trigon® |
| Nominal $\varnothing D$ | 24.5 |
| Maximum adjustment limit V_{max} | 0.5 mm |
| Overhang L_A | 99 mm |
| Drill depth for indexable insert drill up to | 3xD |
| Shank | DIN 6535 HE, DIN 6595 |
| Use for drilling | Centre drilling |
| Use for drilling | limited cross-drilling |
| Use for drilling | oblique spot drilling |
| Use for drilling | limited cross-drilling |
| Use for drilling | Aperture |
| Use for drilling | oblique exit |
| Use for drilling | convex |
| Through-coolant | yes |

Accessories

| | |
|---|-------------|
| PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 6IP | 674252 6IP |
| Torx Plus® insert screw set 10 pieces Drive 6IP2 | 239652 6IP2 |
| Torque screwdriver, fixed setting set torque 1,0 Nm | 211750 1,0 |