



KOMET KUB Centron® drill head, Ø DC: 58 mm



Order data

Order number	236650 58
GTIN	4047109081710
Item class	24L

Description

Version:

- Process reliable up to 8 (9)×D.
- Centring by centring point and slide bars.
- Stiff joint between base body and drill head.
- Ø of the slide bars is matched to indexable inserts with 0.4 mm edge radii. For through holes the Ø of the slide bars can be adjusted by means of shims.

Application:

- For rotating and stationary as well as vertical and horizontal use in all materials.
- With centring tips No. 236655 – 236657.
- With indexable inserts No. 236740 – 237080.

Suitable for :

Base body No. 236652 – 236654.

Supplied with:

Drill head including slide bars (spare slide bars No. 236658).

From Ø 65 mm with indexable insert cartridges (cartridge for the outer indexable insert adjustable + 1 mm on the Ø).

Through-coolant: yes

for inch Ø: 2 9/32 inch

Base body size: 55

Screw for base body: 239655 20IP2

Centring tip size: 46

ISO code indexable insert: WOEX 080404

Pack of insert screws: 239655 15IP (6.3 Nm)

Technical description

Screw for base body	239655 20IP2
Base body size	55
Centring tip size	46
ISO code indexable insert	WOEX 080404
Pack of insert screws	239655 15IP (6.3 Nm)
Series	KUB Centron®
Nominal Ø D	58
for inch Ø	2 9/32 inch
Use for drilling	Centre drilling
Use for drilling	limited cross-drilling
Use for drilling	limited drilling with oblique exit
Use for drilling	limited cross-drilling
Through-coolant	yes

Accessories

KOMET KUB Centron® centring point, carbide Type 46	236657 46
PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 15IP	674252 15IP
Torx Plus® insert screw set 10 pieces Drive 15IP	239655 15IP
KOMET® base body Ø DC 55 mm	236653 55
KOMET KUB Centron® centring point, HSS Type 46	236655 46
Torque screwdriver with scale, to take interchangeable blades maximum torque 1600 cNm	659906 1600
KOMET KUB Centron® centring point, HSS Type 46	236656 46
8 mm blade with magnet with 1/4 inch bit holder overall length 50 mm	659874 50

KOMET® base body Ø DC 55 mm	236652 55
KOMET® base body Ø DC 55 mm	236654 55
Torx Plus® insert screw set 10 pieces Drive 20IP2	239655 20IP2