


KOMET KUB Centron® Powerline drill head, Ø DC: 24 mm

Order data

Order number	236651 24
GTIN	4047109226975
Item class	24L

Description
Version:

The drill point guides the tool precisely on the axis of the hole, thus ensuring both straightness and very high process reliability, with stability in hole depths up to 9×D.

Spot drilling on flat level surfaces without a pilot hole.

Drill head without slide bars and slide bar adjustment.

Application:

For rotating and stationary as well as vertical and horizontal use in all materials.

With centring tip No. 236659.

With indexable inserts No. 236520 – 236576.

Note:

Further sizes available on request.

Through-coolant: yes

Base body size: 20

Screw for base body: 239653 8IP8

Centring tip size: 40

ISO code indexable insert: SOEX 060306

Pack of insert screws: 239652 6IP2 (1.0 Nm)

Technical description

Base body size	20
ISO code indexable insert	SOEX 060306

Pack of insert screws	239652 6IP2 (1.0 Nm)
Centring tip size	40
Screw for base body	239653 8IP8
Series	KUB Centron® Powerline
Nominal Ø D	24
Use for drilling	limited cross-drilling
Use for drilling	limited drilling with oblique exit
Use for drilling	limited cross-drilling
Use for drilling	Drilling blind holes
Through-coolant	yes

Accessories

Torque screwdriver, fixed setting set torque 1,0 Nm	211750 1,0
Torx Plus® insert screw set 10 pieces Drive 8IP8	239653 8IP8
Torx Plus® insert screw set 10 pieces Drive 6IP2	239652 6IP2
PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 6IP	674252 6IP