



KOMET® micro-adjustable drilling head B301, Ø Dmin: 100 mm



Order data

Order number	238301 100
GTIN	4047109005754
Item class	24B

Description

Version:

With ABS® connection B301 and accepts M302 precision turning cartridge.

The smallest adjustment is 0.002 mm on the Ø using the vernier. Central coolant supply to the cutting edge.

Application:

For bores from Ø 29.5 to 199 mm.

For high precision setting, turning cartridge can be adjusted after clamping.

Note:

Please order the suitable precision cartridge No. 238310 (M302) and indexable inserts (see group 26) separately.

Through-coolant: yes

Spindle range: 100 - 121 mm

Overhang L₁: 90 mm

ABS® shank Ø D_s: 80

Application: 238310 60

Insert screw set: 249900 SW10

Technical description

Spindle range	100 - 121 mm
Minimum Ø D _{min}	100
Application	238310 60

ABS® shank Ø D _s	80
Overhang L ₁	90 mm
Insert screw set	249900 SW10
Shank	ABS
Use for drilling	Cross-drilling
Use for drilling	oblique exit
Use for drilling	oblique spot drilling
Through-coolant	yes
Type of product	Boring tool

Accessories

Set of insert screws DIN 913 10-piece Drive SW10	249900 SW10
KOMET® precision cartridge M302 Type 60	238310 60