Garant

eco clamping toolholder, short, right-hand, Shank size / insert size: 16/09 mm



Order data

| Order number | 250004 16/09 |
|--------------|---------------|
| GTIN | 4045197926913 |
| Item class | 21U |

Description

Version:

With internal coolant feed right to the cutting edge. Cooling by means of precision nozzles effectively and efficiently reduces the thermal loading, since the coolant stream is optimally directed between the chip and cutting edge. This results in higher productivity, longer tool life and greater process reliability.

With flank face cooling.

Note:

Coolant transfer only possible in conjunction with GARANT eco system toolholders No. 319001 – 319886 or for shank length < 125 mm plus No. 317900.

Through-coolant: yes ISO code toolholder: DCLNR/L 1616X09 suitable indexable insert: CN.. 09T3.. Functional width L₄: 23 mm Head length L₁: 27 mm Overall length L: 74 mm Shim: 259033 7

Technical description

| Insert size | 9 mm |
|----------------------------|-----------|
| Head length L ₁ | 27 mm |
| Clamp, screw, spring | 259036 12 |
| Shank size | 16 mm |

© Hoffmann GmbH Qualitätswerkzeuge

Data sheet

| Shim screw | 259027 5 |
|---------------------------|-----------------|
| ISO code toolholder | DCLNR/L 1616X09 |
| suitable indexable insert | CN 09T3 |
| Overall length L | 74 mm |
| Shim | 259033 7 |
| Functional width L₄ | 23 mm |
| Application type | right-hand |
| Standard | DIN ISO 5610 |
| Through-coolant | yes |
| Setting angle κ | 95 degrees |
| Type of product | Boring bar |