

Garant

QuickTurn clamping toolholder, left-hand, Shank / insert size: 20/12 mm



Order data

Order number	250015 20/12
GTIN	4045197649850
Item class	21U

Description

Version:

Inserts can be changed without using tools. **Release the stop at the push of a button – change the insert – press the clamp to secure it.**

A simple and convenient way to reduce ancillary times.

Application:

Inserts can be changed without using tools. **Release the stop at the push of a button – change the insert – press the clamp to secure it.**

A simple and convenient way to reduce ancillary times.

Through-coolant: no

ISO code toolholder: DCLNR/L 2025K12

suitable indexable insert: CN.. 1204..

Functional width L_4 : 32 mm

Head length L_1 : 32 mm

Overall length L: 125 mm

Shim: 259031 3

Technical description

Head length L_1	32 mm
suitable indexable insert	CN.. 1204..
Cutting point / joint	20×20 mm
Functional width L_4	32 mm
ISO code toolholder	DCLNR/L 2025K12

Shim	259031 3
Clamp	259038 7
Shim screw	259025 4
Shank size	20 mm
Insert size	12 mm
Overall length L	125 mm
Application type	left-hand
Standard	DIN ISO 5610
Through-coolant	no
Setting angle κ	95 degrees
Type of product	Boring bar

Accessories

Clamping claw	259531
Shim	259201
Shim screw	259171
Clamping claw	259351
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Shim screw Type 4	259025 4
Clamping claw Type 11	259038 11
Clamping claw Type 7	259038 7
Shim Type 3	259031 3