

Garant
Boring bar, steel, right-hand, Shank \varnothing / insert size: 40/16 mm

Order data

Order number	250036 40/16
GTIN	4045197654373
Item class	21T

Description
Version:

PCLNR 95° boring bars for indexable inserts CN..

Through-coolant: yes

Shank \varnothing D_s: 40 mm

ISO code toolholder: A40T PCLNR/L16

Setting angle κ : 95 degrees

suitable indexable insert: CN.. 1606..

Minimum pre-drill \varnothing D_{min}: 50 mm

Centre offset L₃: 27 mm

Technical description

Insert size	16 mm
Centre offset L ₃	27 mm
Lever screw	259018 11
Shim punches pack	259047 4
ISO code toolholder	A40T PCLNR/L16
Shim	259031 35
suitable indexable insert	CN.. 1606..
Shim pins pack	259044 6
Minimum pre-drill \varnothing D _{min}	50 mm
Lever	259015 12

Overall length L	300 mm
Clamping height L ₂	38.5 mm
Setting angle κ	95 degrees
Shank Ø D _s	40 mm
Application type	right-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Lever Type 12	259015 12
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Shim punches set 10 pieces Type 4	259047 4
Shim punches set 10 pieces	259520
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Lever	259060
Shim pins set 10 pieces	259430
Shim Type 35	259031 35
Lever screw	259150
Set of shim pins 10 pieces Type 6	259044 6
Shim	259300
Lever screw Type 11	259018 11