

**Garant**
**Boring bar, steel, right-hand, Shank Ø / insert size: 50/16 mm**

**Order data**

Order number	250036 50/16
GTIN	4045197654380
Item class	21T

**Description**
**Version:**

PCLNR 95° boring bars for indexable inserts CN..

Through-coolant: yes

Shank Ø D<sub>s</sub>: 50 mm

ISO code toolholder: A50U PCLNR/L16

Setting angle κ: 95 degrees

suitable indexable insert: CN.. 1606..

Minimum pre-drill Ø D<sub>min</sub>: 63 mm

Centre offset L<sub>3</sub>: 35 mm

**Technical description**

suitable indexable insert	CN.. 1606..
ISO code toolholder	A50U PCLNR/L16
Minimum pre-drill Ø D <sub>min</sub>	63 mm
Centre offset L <sub>3</sub>	35 mm
Insert size	16 mm
Shim punches pack	259047 4
Shim pins pack	259044 6
Shim	259031 35
Lever screw	259018 11
Lever	259015 12

Overall length L	350 mm
Clamping height L <sub>2</sub>	48 mm
Setting angle κ	95 degrees
Shank Ø D <sub>s</sub>	50 mm
Application type	right-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

## Accessories

Lever Type 12	259015 12
Shim punches set 10 pieces Type 4	259047 4
Shim	259300
Shim punches set 10 pieces	259520
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Lever screw	259150
Shim Type 35	259031 35
Shim pins set 10 pieces	259430
Lever screw Type 11	259018 11
Lever	259060
Set of shim pins 10 pieces Type 6	259044 6