

Garant
Boring bar, steel, left-hand, Shank \varnothing / insert size: 20/09 mm

Order data

Order number	250037 20/09
GTIN	4045197650221
Item class	21T

Description

Boring bar, steel 20/09 mm Shank $\varnothing D_s$: 20 mm
 ISO code toolholder: A20Q PCLNR/L09
 Setting angle κ : 95 degrees
 suitable indexable insert: CN.. 09T3..
 Minimum pre-drill $\varnothing D_{min}$: 25 mm
 Centre offset L_3 : 13 mm

Technical description

Lever screw	259018 9
Centre offset L_3	13 mm
ISO code toolholder	A20Q PCLNR/L09
Minimum pre-drill $\varnothing D_{min}$	25 mm
Insert size	9 mm
suitable indexable insert	CN.. 09T3..
Lever	259015 11
Overall length L	180 mm
Clamping height L_2	18 mm
Setting angle κ	95 degrees
Shank $\varnothing D_s$	20 mm
Application type	left-hand

Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

PrecisionBit for hex, shank E 6.3 Hexagon 2 mm	674242 2
Lever	259050
Lever screw Type 10	259018 10
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Lever screw	259140
Lever Type 11	259015 11