

Garant
Boring bar, steel, left-hand, Shank Ø / insert size: 40/12 mm

Order data

Order number	250037 40/12
GTIN	4045197650252
Item class	21T

Description

Boring bar, steel 40/12 mm Shank Ø D_s: 40 mm
 ISO code toolholder: A40T PCLNR/L12
 Setting angle κ: 95 degrees
 suitable indexable insert: CN.. 1204..
 Minimum pre-drill Ø D_{min}: 50 mm
 Centre offset L₃: 27 mm

Technical description

Lever screw	259018 2
Minimum pre-drill Ø D _{min}	50 mm
Shim pins pack	259044 2
suitable indexable insert	CN.. 1204..
Shim punches pack	259047 2
Lever	259015 2
Centre offset L ₃	27 mm
Insert size	12 mm
Shim	259031 2
ISO code toolholder	A40T PCLNR/L12
Overall length L	300 mm
Clamping height L ₂	38.5 mm

Setting angle κ	95 degrees
Shank $\varnothing D_s$	40 mm
Application type	left-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Shim	259200
Set of shim pins 10 pieces Type 2	259044 2
Shim punches set 10 pieces Type 2	259047 2
Lever screw	259100
Lever	259000
PrecisionBit for hex, shank E 6.3 Hexagon 2 mm	674242 2
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Shim pins set 10 pieces	259400
Lever screw Type 2	259018 2
Shim punches set 10 pieces	259500
Shim Type 2	259031 2
Lever Type 2	259015 2