

Garant

Boring bar, steel, left-hand, Shank Ø / insert size: 40/16 mm



Order data

Order number	250037 40/16
GTIN	4045197654410
Item class	21T

Description

Boring bar, steel 40/16 mm Shank Ø D_s: 40 mm

ISO code toolholder: A40T PCLNR/L16

Setting angle κ: 95 degrees

suitable indexable insert: CN.. 1606..

Minimum pre-drill Ø D_{min}: 50 mm

Centre offset L₃: 27 mm

Technical description

ISO code toolholder	A40T PCLNR/L16
Shim punches pack	259047 4
Shim	259031 35
Centre offset L ₃	27 mm
Insert size	16 mm
Lever	259015 12
Minimum pre-drill Ø D _{min}	50 mm
Lever screw	259018 11
suitable indexable insert	CN.. 1606..
Shim pins pack	259044 6
Overall length L	300 mm
Clamping height L ₂	38.5 mm

Setting angle κ	95 degrees
Shank $\varnothing D_s$	40 mm
Application type	left-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Shim Type 35	259031 35
Lever	259060
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Set of shim pins 10 pieces Type 6	259044 6
Lever screw	259150
Shim punches set 10 pieces Type 4	259047 4
Shim	259300
Shim pins set 10 pieces	259430
Lever Type 12	259015 12
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Shim punches set 10 pieces	259520
Lever screw Type 11	259018 11