

**Garant**
**Boring bar, steel, left-hand, Shank Ø / insert size: 50/16 mm**

**Order data**

Order number	250037 50/16
GTIN	4045197654427
Item class	21T

**Description**

Boring bar, steel 50/16 mm Shank Ø D<sub>s</sub>: 50 mm  
 ISO code toolholder: A50U PCLNR/L16  
 Setting angle κ: 95 degrees  
 suitable indexable insert: CN.. 1606..  
 Minimum pre-drill Ø D<sub>min</sub>: 63 mm  
 Centre offset L<sub>3</sub>: 35 mm

**Technical description**

Shim pins pack	259044 6
Lever	259015 12
Insert size	16 mm
Lever screw	259018 11
Shim	259031 35
Shim punches pack	259047 4
ISO code toolholder	A50U PCLNR/L16
Centre offset L <sub>3</sub>	35 mm
Minimum pre-drill Ø D <sub>min</sub>	63 mm
suitable indexable insert	CN.. 1606..
Overall length L	350 mm
Clamping height L <sub>2</sub>	48 mm

Setting angle $\kappa$	95 degrees
Shank $\varnothing D_s$	50 mm
Application type	left-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

## Accessories

Lever	259060
Shim punches set 10 pieces	259520
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Shim Type 35	259031 35
Shim pins set 10 pieces	259430
Set of shim pins 10 pieces Type 6	259044 6
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Lever Type 12	259015 12
Lever screw Type 11	259018 11
Shim	259300
Shim punches set 10 pieces Type 4	259047 4
Lever screw	259150