

## Garant

### QuickTurn clamp toolholder, left-hand, Shank / insert size: 20/11 mm



#### Order data

Order number	250607 20/11
GTIN	4045197650405
Item class	21U

#### Description

##### Advantage:

Inserts can be changed without using tools. **Release the stop at the push of a button – change the insert – press the clamp to secure it.**

A simple and convenient way to reduce non-productive times.

Consistent clamping force, high interchange accuracy, maintenance-free.

##### Application:

Inserts can be changed without using tools. **Release the stop at the push of a button – change the insert – press the clamp to secure it.**

A simple and convenient way to reduce non-productive times.

Consistent clamping force, high interchange accuracy, maintenance-free.

Through-coolant: no

ISO code toolholder: DDJNR/L 2025K11

suitable indexable insert: DN.. 1104..

Functional width L<sub>4</sub>: 32 mm

Head length L<sub>1</sub>: 48.5 mm

Overall length L: 125 mm

Shim: 259031 8

#### Technical description

suitable indexable insert	DN.. 1104..
Shank size	20 mm
Insert size	11 mm
Clamp	259038 6

Functional width L <sub>4</sub>	32 mm
ISO code toolholder	DDJNR/L 2025K11
Head length L <sub>1</sub>	48.5 mm
Shim screw	259025 5
Shim	259031 8
Overall length L	125 mm
Application type	left-hand
Standard	DIN ISO 5610
Through-coolant	no
Setting angle κ	93 degrees
Type of product	Boring bar

## Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Shim	259211
Shim screw	259174
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Shim screw Type 5	259025 5
Clamping claw Type 6	259038 6
Shim Type 8	259031 8
Clamping claw	259350