

Garant
QuickTurn clamp toolholder, left-hand, Shank / insert size: 20/15 mm

Order data

Order number	250607 20/15
GTIN	4045197650429
Item class	21U

Description
Advantage:

Inserts can be changed without using tools. **Release the stop at the push of a button – change the insert – press the clamp to secure it.**

A simple and convenient way to reduce non-productive times.

Consistent clamping force, high interchange accuracy, maintenance-free.

Application:

Inserts can be changed without using tools. **Release the stop at the push of a button – change the insert – press the clamp to secure it.**

A simple and convenient way to reduce non-productive times.

Consistent clamping force, high interchange accuracy, maintenance-free.

Through-coolant: no

ISO code toolholder: DDJNR/L 2025K15

suitable indexable insert: DN.. 1506..

Functional width L₄: 32 mm

Head length L₁: 46 mm

Overall length L: 125 mm

Shim: 259031 29

Technical description

Cutting point / joint	20×20 mm
Shank size	20 mm
ISO code toolholder	DDJNR/L 2025K15
Insert size	15 mm

Head length L ₁	46 mm
Functional width L ₄	32 mm
Shim screw	259025 4
Clamp	259038 7
suitable indexable insert	DN.. 1506..
Shim	259031 29
Overall length L	125 mm
Application type	left-hand
Standard	DIN ISO 5610
Through-coolant	no
Setting angle κ	93 degrees
Type of product	Boring bar

Accessories

Shim screw	259171
Shim	259271
Clamping claw	259351
Clamping claw	259350
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Clamping claw Type 7	259038 7
Clamping claw Type 6	259038 6
Shim Type 29	259031 29
Shim screw Type 4	259025 4