


Garant
eco clamp toolholder, short, left-hand, Shank size / insert size: 20/15 mm


Order data

Order number	250615 20/15
GTIN	4045197927330
Item class	21U

Description

Version:

With internal coolant feed right to the cutting edge. Cooling by means of precision nozzles effectively and efficiently reduces the thermal loading, since the coolant stream is optimally directed between the chip and cutting edge. This results in higher productivity, longer tool life and increased process reliability.

Note:

Coolant transfer only possible in conjunction with GARANT eco system toolholders No. 319001 – 319886 or for shank length < 125 mm plus No. 317900.

Through-coolant: yes

ISO code toolholder: DDJNR/L 2020X15

suitable indexable insert: DN.. 1506..

Functional width L₄: 25 mm

Head length L₁: 38 mm

Overall length L: 97 mm

Shim: 259033 3

Technical description

Functional width L ₄	25 mm
ISO code toolholder	DDJNR/L 2020X15
Insert size	15 mm
suitable indexable insert	DN.. 1506..
Clamp, screw, spring	259036 11

Shank size	20 mm
Shim	259033 3
Head length L ₁	38 mm
Shim screw	259027 2
Overall length L	97 mm
Application type	left-hand
Standard	DIN ISO 5610
Through-coolant	yes
Setting angle κ	93 degrees
Type of product	Boring bar

Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX10	674248 TX10
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500