

## Garant

### QuickTurn clamp toolholder, right-hand, Shank / insert size: 20/12 mm



## Order data

Order number	251104 20/12
GTIN	4045197650757
Item class	21U

## Description

### Advantage:

Inserts can be changed without using tools. **Release the stop at the push of a button – change the insert – press the clamp to secure it.**

A simple and convenient way to reduce non-productive times.

Consistent clamping force, high interchange accuracy, maintenance-free.

### Application:

Inserts can be changed without using tools. **Release the stop at the push of a button – change the insert – press the clamp to secure it.**

A simple and convenient way to reduce non-productive times.

Consistent clamping force, high interchange accuracy, maintenance-free.

Through-coolant: no

ISO code toolholder: DSSNR/L 2025K12

suitable indexable insert: SN.. 1204..

Functional width L<sub>4</sub>: 32 mm

Head length L<sub>1</sub>: 49 mm

Overall length L: 125 mm

Shim: 259031 21

## Technical description

Shim screw	259025 4
Functional width L <sub>4</sub>	32 mm
Shank size	20 mm
Shim	259031 21

Cutting point / joint	20×20 mm
Insert size	12 mm
Clamp	259038 8
suitable indexable insert	SN.. 1204..
Head length L <sub>1</sub>	49 mm
ISO code toolholder	DSSNR/L 2025K12
Overall length L	125 mm
Application type	right-hand
Standard	DIN ISO 5610
Through-coolant	no
Setting angle κ	45 degrees
Type of product	Boring bar

## Accessories

Shim	259231
Shim screw	259171
Clamping claw	259352
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Shim screw Type 4	259025 4
Shim Type 21	259031 21
Clamping claw Type 8	259038 8