

Garant

QuickTurn clamp toolholder, right-hand, Shank / insert size: 25/12 mm



Order data

Order number	251104 25/12
GTIN	4045197650764
Item class	21U

Description

Advantage:

Inserts can be changed without using tools. **Release the stop at the push of a button – change the insert – press the clamp to secure it.**

A simple and convenient way to reduce non-productive times.

Consistent clamping force, high interchange accuracy, maintenance-free.

Application:

Inserts can be changed without using tools. **Release the stop at the push of a button – change the insert – press the clamp to secure it.**

A simple and convenient way to reduce non-productive times.

Consistent clamping force, high interchange accuracy, maintenance-free.

Through-coolant: no

ISO code toolholder: DSSNR/L 2525M12

suitable indexable insert: SN.. 1204..

Functional width L_4 : 32 mm

Head length L_1 : 49 mm

Overall length L: 150 mm

Shim: 259031 21

Technical description

Shim screw	259025 4
Insert size	12 mm
Clamp	259038 8
Functional width L_4	32 mm

suitable indexable insert	SN.. 1204..
Head length L ₁	49 mm
Shim	259031 21
ISO code toolholder	DSSNR/L 2525M12
Cutting point / joint	25×25 mm
Shank size	25 mm
Overall length L	150 mm
Application type	right-hand
Standard	DIN ISO 5610
Through-coolant	no
Setting angle κ	45 degrees
Type of product	Boring bar

Accessories

Shim screw	259171
Shim	259231
Clamping claw	259352
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Clamping claw Type 8	259038 8
Shim Type 21	259031 21
Shim screw Type 4	259025 4