

Garant
QuickTurn clamp toolholder, left-hand, Shank / insert size: 20/12 mm

Order data

Order number	251105 20/12
GTIN	4045197650771
Item class	21U

Description
Advantage:

Inserts can be changed without using tools. **Release the stop at the push of a button – change the insert – press the clamp to secure it.**

A simple and convenient way to reduce non-productive times.

Consistent clamping force, high interchange accuracy, maintenance-free.

Application:

Inserts can be changed without using tools. **Release the stop at the push of a button – change the insert – press the clamp to secure it.**

A simple and convenient way to reduce non-productive times.

Consistent clamping force, high interchange accuracy, maintenance-free.

Through-coolant: no

ISO code toolholder: DSSNR/L 2025K12

suitable indexable insert: SN.. 1204..

Functional width L_4 : 32 mm

Head length L_1 : 49 mm

Overall length L: 125 mm

Shim: 259031 21

Technical description

Shim	259031 21
Shim screw	259025 4
Cutting point / joint	20×20 mm
Shank size	20 mm

Functional width L ₄	32 mm
suitable indexable insert	SN.. 1204..
ISO code toolholder	DSSNR/L 2025K12
Insert size	12 mm
Clamp	259038 8
Head length L ₁	49 mm
Overall length L	125 mm
Application type	left-hand
Standard	DIN ISO 5610
Through-coolant	no
Setting angle κ	45 degrees
Type of product	Boring bar

Accessories

Shim screw	259171
Shim	259231
Clamping claw	259352
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Shim Type 21	259031 21
Clamping claw Type 8	259038 8
Shim screw Type 4	259025 4