

**Garant**
**Lever lock toolholder, right-hand, Shank / insert size: 25/12 mm**

**Order data**

|              |               |
|--------------|---------------|
| Order number | 251112 25/12  |
| GTIN         | 4045197650863 |
| Item class   | 21T           |

**Description**

Lever lock toolholder right-hand 25/12 mm ISO code toolholder: PSSNR/L 2525M12  
 suitable indexable insert: SN.. 1204..  
 Functional width L<sub>4</sub>: 32 mm  
 Head length L<sub>1</sub>: 29 mm  
 Overall length L: 150 mm  
 Shim: 259031 20

**Technical description**

|                                 |                 |
|---------------------------------|-----------------|
| Lever                           | 259015 2        |
| Head length L <sub>1</sub>      | 29 mm           |
| ISO code toolholder             | PSSNR/L 2525M12 |
| Functional width L <sub>4</sub> | 32 mm           |
| suitable indexable insert       | SN.. 1204..     |
| Insert size                     | 12 mm           |
| Shim                            | 259031 20       |
| Shank size                      | 25 mm           |
| Shim pins pack                  | 259044 2        |
| Lever screw                     | 259018 2        |
| Shim punches pack               | 259047 2        |

|                        |              |
|------------------------|--------------|
| Overall length L       | 150 mm       |
| Application type       | right-hand   |
| Standard               | DIN ISO 5610 |
| Through-coolant        | no           |
| Setting angle $\kappa$ | 45 degrees   |
| Type of product        | Boring bar   |

## Accessories

|  |            |
|--|------------|
| Shim punches set 10 pieces   | 259500     |
| Lever  | 259000     |
| Lever screw Type 2   | 259018 2   |
| Shim Type 20   | 259031 20  |
| Lever Type 2   | 259015 2   |
| Set of shim pins 10 pieces Type 2  | 259044 2   |
| Shim punches set 10 pieces Type 2  | 259047 2   |
| Shim pins set 10 pieces  | 259400     |
| Shim   | 259230     |
| Lever screw  | 259100     |
| Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm | 659906 500 |
| PrecisionBit for hex, shank E 6.3 Hexagon 3 mm                                       | 674242 3   |