

**Garant**
**Boring bar, steel, right-hand, Shank  $\varnothing$  / insert size: 40/16 mm**

**Order data**

Order number	251720 40/16
GTIN	4045197867162
Item class	21T

**Description**

Boring bar, steel 40/16 mm Shank  $\varnothing$  D<sub>3</sub>: 40 mm  
 ISO code toolholder: A40T MVPNR/L 16  
 Setting angle  $\kappa$ : 117.5 degrees  
 suitable indexable insert: VN.. 1604..  
 Minimum pre-drill  $\varnothing$  D<sub>min</sub>: 50 mm  
 Centre offset L<sub>3</sub>: 27 mm

**Technical description**

Setting angle $\kappa$	117.5 degrees
Shim	259031 39
Minimum pre-drill $\varnothing$ D <sub>min</sub>	50 mm
Screw for clamp	259021 1
Clamping claw	259038 2
suitable indexable insert	VN.. 1604..
Overall length L	300 mm
Clamping height L <sub>2</sub>	38.5 mm
ISO code toolholder	A40T MVPNR/L 16
Centre offset L <sub>3</sub>	27 mm
Insert size	16 mm
Shim screw	259025 3

Shank $\varnothing D_s$	40 mm
Application type	right-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

## Accessories

Shim	259310
Clamping claw Type 2	259038 2
Shim Type 39	259031 39
Clamping claw	259320
Screw for clamping claw	259180
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Shim screw	259170
Shim screw Type 3	259025 3
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Screw for clamping claw Type 1	259021 1