

Garant
Boring bar, steel, left-hand, Shank Ø / insert size: 32/16 mm

Order data

Order number	251721 32/16
GTIN	4045197867186
Item class	21T

Description

Boring bar, steel 32/16 mm Shank Ø D_s: 32 mm
 ISO code toolholder: A32S MVPNR/L 16
 Setting angle κ: 117.5 degrees
 suitable indexable insert: VN.. 1604..
 Minimum pre-drill Ø D_{min}: 40 mm
 Centre offset L₃: 22 mm

Technical description

Setting angle κ	117.5 degrees
Shim	259031 39
Clamping height L ₂	31 mm
Screw for clamp	259021 4
Clamping claw	259038 2
Minimum pre-drill Ø D _{min}	40 mm
Centre offset L ₃	22 mm
Shim screw	259025 3
ISO code toolholder	A32S MVPNR/L 16
Insert size	16 mm
suitable indexable insert	VN.. 1604..
Overall length L	250 mm

Shank $\varnothing D_s$	32 mm
Application type	left-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Shim	259310
Screw for clamp	259184
Shim Type 39	259031 39
Screw for clamping claw Type 4	259021 4
Clamping claw Type 2	259038 2
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Shim screw	259170
Shim screw Type 3	259025 3
Clamping claw	259320
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8